

---

# How To True A Bike Wheel

---

Downloaded from  
*How To True A Bike Wheel* [everybodystreet.com](http://everybodystreet.com)  
by Angie & Alexis

---

## INTRODUCTION: WHY WHEEL TRUING MATTERS FOR EVERY CYCLIST

---

A wobbly wheel is one of the most frustrating issues a cyclist can face. It can cause brake rub, uneven tire wear, and a noticeable loss of control, especially at higher speeds. Fortunately, learning **how to true a bike wheel** is a skill that saves time, money, and keeps your ride smooth. While many riders assume wheel truing is a job for

a professional mechanic, the reality is that with a few basic tools and a methodical approach, you can restore a bent rim to near-perfect condition in your own workshop. This guide will walk you through the entire process, from identifying a warped wheel to adjusting spoke tension with confidence.

Wheel truing is not just about fixing a visible wobble—it is also about maintaining even spoke tension, which extends the life of your wheels and improves overall bike performance. Whether

you are a weekend commuter or a competitive racer, understanding **how to true a bike wheel** empowers you to solve problems on the road and at home. In the sections below, we will cover the anatomy of a wheel, the tools required, step-by-step truing procedure, and advanced tips for achieving perfect centering. By the end, you will have the knowledge to tackle both minor tweaks and more significant rim corrections.

---

## UNDERSTANDING WHEEL ANATOMY AND COMMON ISSUES

---

### The Role

# of Spokes and Nipples

Every wheel consists of a hub, spokes, nipples, and a rim. Spokes connect the hub to the rim and are tensioned to create a rigid structure. When a wheel is out of true, it means the rim no longer rotates in a flat plane, either side-to-side (lateral deflection) or up-and-down (radial deflection). Lateral wobble is the most common issue and the primary focus when learning **how to true a bike wheel**. Each spoke has a nipple at the rim end that can be turned with a spoke wrench to increase or decrease tension. Tightening a spoke

pulls the rim toward that side, while loosening allows the rim to move away. Understanding this pulling effect is the foundation of truing.

## Common Causes of Wheel Wobble

- **Impact damage:** Hitting a pothole, curb, or rock can bend the rim or break spokes.
- **Uneven spoke tension:** New wheels may settle, or wheels that have never been maintained can develop loose spokes.
- **Rim wear:** Over

time, braking surfaces wear unevenly, causing false wobbles that look like truing issues but are actually thickness variations.

- **Spoke fatigue:** A single broken spoke can instantly throw the wheel out of alignment.

Before you begin truing, inspect the rim for cracks, dents, or severely bent sections. A rim that is structurally compromised should be replaced, not trued. For minor bends, **how to true a bike wheel** becomes a precise adjustment process.

---

### TOOLS YOU NEED

## TRUING

Having the right equipment makes the difference between a successful truing and a frustrating struggle. Here is a list of essential tools:

1. **Spoke wrench:**

Choose the correct size for your nipples (commonly 3.2mm, 3.3mm, or 3.5mm). A four-sided spoke wrench is ideal because it reduces the chance of stripping the nipple.

2. **Truing stand:**

While you can use the bike frame itself as a makeshift stand, a dedicated truing stand with adjustable

calipers make the job far easier

and more accurate. Popular options include models from Park Tool, Feedback Sports, or Minoura.

3. **Spoke tension meter:**

Not essential for beginners, but very helpful for achieving even tension across all spokes. Consistent tension is as important as lateral and radial trueness.

4. **Lubricant (e.g., WD-40 or light oil):**

Apply a drop to each nipple spoke thread if the wheel is old or corroded. This prevents nipples from seizing as

you turn them.

5. **Truing stand adapters or a zip tie:** If using the bike frame, attach a zip tie to the seat stay or fork as a fixed reference point to gauge the wobble.
6. **Ruler or caliper:** For measuring rim offset from the frame or truing stand calipers.

Once you have these tools, you are ready to learn **how to true a bike wheel** systematically.

---

### STEP-BY-STEP GUIDE: HOW TO TRUE A BIKE WHEEL

---

## Step 1: Mount the Wheel and Identify the Wobble

Place the wheel into your truing stand (or mount it on the bike and use a zip tie as a pointer). Tighten the stand's calipers to just barely touch the rim at the point of greatest lateral deviation. Spin the wheel slowly and watch where the rim moves toward the caliper. If you are using

the bike method, attach the zip tie to the frame so its tip is about 2mm from the rim's side. As the wheel rotates, the gap will change; the areas where the rim touches or moves away from the zip tie are the spots that need correction.

## Step 2: Locate the Problem Area and Determine

## Direction

Mark the worst wobble with a piece of tape or a marker. The rim moves either left or right relative to the centerline. If the rim shifts to the right, it means the right side spokes are too tight relative to the left side (or the left side is too loose). The rule is simple: to move the rim to the left, tighten left side spokes or loosen right side spokes. Always remember that tightening a spoke pulls the rim toward that side, and loosening pushes it away.

## Step 3:

# Work in Small Adjustments

Using your spoke wrench, turn the nipples in quarter-turn increments. Do not tighten or loosen more than a half turn at a time; massive changes can cause new problems like detensioning neighboring spokes or creating a radical hop. Focus on the center of the wobble area. For a lateral deviation of 2–3 mm, start with the spokes at the apex of the bend. Tighten the side opposite the direction you want to move the rim. For example, if the rim

bows to the right, tighten the left-side spokes in that region (or loosen the right-side spokes slightly). After three or four quarter-turns, spin the wheel and check progress.

## Step 4: Check Radial Trueness (Roundness)

Sometimes wobble involves the rim moving up and down (a “hop”) as well. Adjust the truing stand calipers to touch the rim from the top or bottom (radial check).

If the rim lifts upward (toward the top caliper), tighten spokes on both sides equally in that area—this pulls the rim down. Conversely, if the rim dips downward, loosen both sides to allow the rim to rise. Radial adjustments must be balanced to avoid introducing lateral wobble. A good rule: each quarter turn of both sides changes rim radius by roughly 0.1–0.2 mm.

## Step 5: Even Out Spoke Tension

Once the rim is relatively straight (within 0.5 mm lateral and 1 mm radial), use

a tension meter to check spoke tensions. Aim for all spokes on the same side to be within 10–15% of each other. If you do not have a tension meter, pluck the spokes like guitar strings; they should sound similar. Uneven tension leads to future failure. Learning **how to true a bike wheel** includes developing a feel for balanced tension. If you find a spoke that is very tight, loosen its neighbors slightly and tighten the loose spoke.

## Step 6: Repeat and

## MISTAKES TO Refine

Truing is an iterative process. After adjusting a group of spokes, spin the wheel and reassess. The rim will gradually come into alignment. Be patient—small corrections compound. A perfect true might require going around the wheel three or four times. When the rim no longer touches the caliper at any point during rotation (or barely kisses it in the same spot on both sides), you have achieved a satisfactory true. Do not aim for absolute perfection on your first attempt; a 0.5 mm lateral runout is acceptable for most riding.

---

### COMMON

### AVOID WHEN TRUING A WHEEL

---

- **Over-tightening:** When learning **how to true a bike wheel**, it is tempting to crank spokes to force the rim into shape. This can damage nipples, crack the rim, or snap spokes. Use gentle, even torque.
- **Ignoring spoke tension balance:** A wheel can be perfectly true but have wildly uneven tension, causing it to go out of true after a few rides. Always check tension after truing.
- **Truing a**

**severely bent**

**rim:** If the rim has a permanent dent or a flat spot, truing will not fix it. In that case, replace the rim or the entire wheel.

- **Forgetting to lubricate**

**nipples:**

Especially on older wheels, corroded nipples can strip or seize. A drop of penetrating oil makes adjustments smoother.

- **Not checking dish**

**(centering):**

After truing, the wheel might be centered relative to the hub but not relative to the frame. Use a dishing tool to ensure the rim is

precisely between the locknuts.

---

## **ADVANCED TIPS FOR PROFESSIONAL- LEVEL RESULTS**

---

# Using a Dishing Tool and Centering the Wheel

A dishing tool (or simply flipping the wheel in the truing stand) allows you to check whether the rim is offset from the centerline. If you true the wheel only laterally in the stand, you might

end up with a rim that is shifted left relative to the hub. This can cause misalignment with the brake calipers and poor handling. After initial truing, use a dishing tool to compare the distance from the rim to the locknut on both sides. Adjust spoke tension on the side that is too far out to bring the rim back to center. This step is critical for wheels with off-center hubs (e.g., rear wheels with a cassette).

## Dealing with a Broken Spoke

A broken spoke requires replacement before truing. Remove

the broken spoke and install a new one of the same length and gauge. Thread the new spoke through the hub flange and nipple, then tighten it to approximate tension based on adjacent spokes. Then proceed with the truing process. A single new spoke can significantly alter wheel balance, so be prepared to adjust many neighbors.

## When to Seek Professional Help

While **how to true a bike wheel** is learnable, some situations warrant a bike shop: catastrophic rim damage, extreme

wobble ( $>5$  mm), carbon fiber rims (which are more fragile), or if you lack the patience or tools. Professional mechanics can also rebuild a wheel entirely if needed. However, for routine maintenance, self-truing is highly rewarding.

---

### **CONCLUSION: MASTERING WHEEL TRUING SAVES MONEY AND ENHANCES SAFETY**

---

Learning **how to true a bike wheel** is an essential skill for any cyclist who wants to maintain a reliable, smooth ride. By understanding the relationship between spoke tension and rim

position, and by using the correct tools and a methodical approach, you can correct most lateral and radial wobbles in under an hour. Not only does this save you the cost of frequent shop visits, but it also gives you a deeper connection with your bike. A properly trued wheel ensures even brake pad contact, reduces vibration, and prevents unnecessary stress on spokes and rims. As with any mechanical skill, practice builds proficiency—so do not be discouraged if your first few attempts are imperfect. With the steps outlined in this guide, you now have a clear roadmap to true wheels confidently and safely.