

How Does A Supercharger Work

How Does A Supercharger Work

Downloaded from everybodystreet.com by Ballard & Whitaker

INTRODUCTION: THE QUEST FOR MORE POWER

For as long as there have been internal combustion engines, enthusiasts and engineers have sought ways to make them more powerful. While increasing engine displacement was the traditional route, it comes with significant weight and packaging penalties. A more elegant solution is forced induction, a method of artificially increasing the density of the air entering the engine. Among the forced induction family, the supercharger stands out for its immediate, linear power delivery and unmistakable whine. But how does a supercharger work? This article provides a comprehensive, detailed look at the mechanics, types, benefits, and trade-offs of this remarkable device, demystifying the engineering that forces an engine to breathe deeper and produce significantly more horsepower.

UNDERSTANDING THE CORE CONCEPT: FORCED INDUCTION VS. NATURALLY ASPIRATED

To fully grasp how a supercharger functions, one must first understand the basic premise of a four-stroke engine. An engine is fundamentally an air pump. The power it produces is directly related to the amount of air and fuel it can combust. A naturally aspirated (NA) engine relies solely on atmospheric pressure to draw air into its cylinders. When a piston moves down, it creates a vacuum, and air rushes in to fill the void. However, this process is inherently limited by ambient air pressure (approximately 14.7 psi at sea level). You cannot force more air into the cylinder than the pressure of the atmosphere without external help.

A supercharger solves this limitation. It is a mechanical air compressor that is belt-driven, gear-driven, or chain-driven directly by the engine's crankshaft. Because it is mechanically linked to the engine, it spins at a ratio of the engine's RPM, providing immediate boost pressure the moment the throttle is opened. This is the key differentiator from a turbocharger, which is powered by exhaust gas and experiences a delay known as "turbo lag." When we ask, "how does a supercharger work?", the simplest answer is: it is a pump, mechanically driven by the engine, that forces more air into the combustion chamber than the engine could draw on its own.

THE ANATOMY OF A SUPERCHARGER SYSTEM

Before diving into types, it is important to understand the common components that make up a typical supercharger installation. While designs vary, most systems share these key parts:

- **The Compressor Unit:** This is the core of the system, the actual air-moving device, which

can be a Roots-type, twin-screw, or centrifugal unit.

- **The Drive Mechanism:** A belt (most common), chain, or gears connecting the supercharger pulley to the engine's crankshaft pulley.
- **The Boost Reference Pulley:** The pulley size is critical. A smaller pulley on the supercharger makes it spin faster relative to the engine, producing higher boost pressure.
- **The Intake Plenum:** The space where compressed air is collected before being distributed to the engine's intake runners.
- **The Intercooler (Optional but Common):** A heat exchanger that cools the compressed air before it enters the engine. Compressing air generates significant heat, which can lead to detonation (knock). An intercooler lowers the intake air temperature, increasing density and safety.
- **By-Pass Valve (also known as a Blow-Off Valve or Recirculation Valve):** This is a crucial component for driveability. When the throttle plate closes suddenly (e.g., during a gear shift), the supercharger is still spinning and creating boost. Without a bypass valve, this pressurized air has nowhere to go, causing a pressure surge that can damage the supercharger or the throttle body. The bypass valve opens to recirculate the boost back to the intake of the supercharger or vent it to the atmosphere.
- **Fuel System Upgrades:** Adding more air requires more fuel. A supercharger installation almost always necessitates larger fuel injectors, a higher-flow fuel pump, and a tune for the engine control unit (ECU).

THE THREE MAIN TYPES OF SUPERCHARGERS

There is not a single answer to the question, "how does a supercharger work?" because the technology has evolved into three primary designs, each with its own strengths and characteristics. Understanding these differences is key to selecting the right system for a specific application.

1. Roots-Type Supercharger

The Roots blower is the oldest and most visually iconic supercharger design. It is named after the Roots brothers who invented it in the 1860s as an air mover for blast furnaces, not initially for engines. How does a Roots supercharger work? It consists of two meshing lobes (typically with two or three lobes each) that rotate inside a close-fitting housing. As the lobes rotate, they trap air on the inlet side and carry it around to the outlet side. Critically, the air is not compressed inside the supercharger itself. Instead, it is simply moved from the intake to the plenum, where it is forced into the engine. This is often described as a "fixed-displacement" air pump.

Key Characteristics:

- **Instant Boost:** Because it is a positive displacement pump, it moves a fixed volume of air per revolution. This provides immediate boost from low RPM, making the engine feel responsive and powerful right off idle.
- **Heat Generation:** The Roots design is inherently inefficient. It does not compress air internally; instead, it pressurizes the plenum by forcing air against the engine's intake. This process is thermodynamically inefficient and generates significant heat. Inefficient heat leads to a greater need for intercooling.
- **Distinctive Sound:** Roots superchargers are famous for their loud, aggressive, whining or "screaming" sound, especially at higher RPM. This is often a desirable trait for muscle cars and hot rods.
- **Torque Monster:** They produce massive torque at low and mid-range RPMs, providing a thrilling surge of power. This makes them ideal for street-driven cars and applications like large-displacement V8s.
- **Common Applications:** They are most commonly seen on American V8s (e.g., Shelby GT500, Dodge Hellcat) and in many classic hot rods.

2. Twin-Screw Supercharger

The twin-screw supercharger is often misidentified as a Roots blower, but it operates on a fundamentally different principle. While it also uses two rotating elements, the rotors are shaped more like archimedean screws. How does a twin-screw supercharger work? The key difference is that a twin-screw unit compresses air internally. As the two helical rotors (typically male and female) mesh, the space between them decreases as the air is moved from the inlet to the outlet. This creates internal compression before the air is discharged into the plenum. This is a form of positive displacement with internal compression, which makes it significantly more efficient than a Roots blower.

Key Characteristics:

- **High Efficiency:** Because it compresses the air internally, it generates less heat than a Roots-type for the same amount of boost. This allows for less reliance on a massive intercooler and reduces parasitic losses.
- **Excellent Low-End Torque:** Like the Roots, it is a positive displacement pump, so it provides instant, powerful boost from idle to redline.
- **Quieter Operation (Relatively):** While still audible, a twin-screw unit is generally less loud and less whiny than a Roots blower. It produces a lower-pitched, more mechanical hum.
- **More Compact:** The design is often more compact than a comparable Roots unit, making it easier to package under a low hood.
- **Common Applications:** These are a popular upgrade for European performance cars (e.g., Audi, BMW, Mercedes) as well as many American V8 applications where a balance of power

and efficiency is desired. The Eaton TVS (Twin Vortices Series) is a modern, highly advanced twin-screw design used on many factory supercharged cars.

3. Centrifugal Supercharger

The centrifugal supercharger is a completely different animal. It looks similar to a turbocharger compressor side, but is mechanically driven by a belt. How does a centrifugal supercharger work? It uses an impeller - a fan-like wheel with curved blades - that spins at extremely high speeds (up to 60,000+ RPM) to draw air in. This air is then accelerated outwards by centrifugal force, where it enters a volute casing. The volute is a spiral-shaped housing that converts the high-speed, low-pressure air into low-speed, high-pressure air (this is known as dynamic compression).

Key Characteristics:

- **Dynamic Compression:** Unlike positive displacement units, the boost pressure produced by a centrifugal supercharger is exponential. It produces very little boost at low RPM, but it builds rapidly as the engine revs higher. This results in a power curve that feels very much like a large turbocharger, but without the lag of a turbo.
- **High Top-End Power:** The centrifugal design is exceptionally efficient at high RPM. It can generate massive horsepower numbers at the top of the rev range, making it ideal for racing applications where high-speed performance is king.
- **Low Parasitic Loss:** Because it doesn't move a fixed volume of air per revolution and only creates significant load when the impeller is spinning very fast, it has the lowest parasitic drag on the engine at low RPM. This translates to better fuel economy during normal driving compared to Roots or twin-screw units.
- **Quiet Operation:** The only sound is a subtle turbine whine, which is much less intrusive than the gear whine of a Roots. This appeals to those who want power without the obvious visual or auditory signature.
- **Ease of Installation:** Many centrifugal units are designed as "self-contained" kits that are relatively easy to install on a wide range of engines, often requiring less significant modification to the hood or front accessory drive.
- **Common Applications:** They are very popular for late-model Mustangs, Camaros, and imports (e.g., Honda, Nissan). They are also the supercharger of choice for many track-day cars and competitive drag racing classes.

PROS AND CONS: IS A SUPERCHARGER RIGHT FOR YOU?

Understanding how a supercharger works is only part of the decision. Weighing its advantages against its disadvantages is crucial for any performance enthusiast.

Advantages

- **Immediate Throttle Response:** By far the biggest benefit. No lag. The power is directly tied to engine RPM, making for an incredibly linear and predictable power delivery.
- **Low-End Torque:** Positive displacement superchargers (Roots and Twin-Screw) provide tremendous low-RPM torque, making a car feel incredibly strong from a standstill.
- **Broad Power Band:** A well-matched supercharger can provide a much wider power band than a turbocharger of a similar size, delivering usable power across the entire rev range.
- **Reliability (Generally):** Because they are mechanically driven and not subjected to the extreme heat of exhaust gas, superchargers are often more reliable and have longer service intervals than turbochargers.

- **Simplicity of Installation (Some Kits):** Many modern centrifugal kits are relatively straightforward to install compared to a complex turbo system.

Disadvantages

- **Parasitic Loss:** This is the primary efficiency disadvantage. The supercharger draws power directly from the crankshaft to turn itself. It can consume 15-20% of the engine's gross horsepower just to drive it. The net gain is the increase in air density minus this loss. This mechanical drag is the price you pay for instant boost.
- **Heat Generation:** Compressing air generates heat. Without an efficient intercooler, the intake air