

# How To Build Radionics Machine

How To Build Radionics Machine

Downloaded from [everybodystreet.com](http://everybodystreet.com) by Neil & Brody

## UNDERSTANDING RADIONICS AND ITS APPLICATIONS

Radionics is a fascinating field that bridges the gap between conventional electronics and subtle energy healing modalities. The term itself evokes curiosity, often leading to questions about how to build a radionics machine from scratch. For many practitioners and hobbyists, constructing their own device is not just a cost-saving measure but a deeply personal journey into understanding the underlying principles of resonance, frequency, and intention. This guide will walk you through the theoretical foundations, essential components, and practical steps needed to assemble a functional radionics device, whether you are a complete beginner or an experienced experimenter.

The concept of radionics rests on the premise that every living organism emits a unique energy field or frequency pattern. When this field becomes imbalanced, it can manifest as physical or emotional distress. A radionics machine is designed to detect these imbalances and broadcast corrective frequencies to restore harmony. While mainstream science often views radionics with skepticism due to its reliance on the "observer effect" and subtle energies, thousands of practitioners worldwide attest to its efficacy in areas such as dowsing, vibrational healing, and agricultural enhancement. Building your own machine allows you to tailor the device to your specific needs and philosophical approach, making the learning process both rewarding and enlightening.

## CORE PRINCIPLES BEHIND RADIONICS MACHINES

### The Role of Frequency and Resonance

At the heart of every radionics device lies the principle of sympathetic vibration. Every substance, from a simple mineral to a complex organ, is believed to have a characteristic frequency. When you intend to treat a condition, you are essentially matching the altered frequency of the affected area with a known healthy frequency. This is why understanding how to build a radionics machine begins with studying frequency tables and rate books. The machine acts as a bridge between your intention and the subtle energy field of the subject, amplifying the desired resonance without requiring physical contact.

### The Importance of Intention and The Operator Effect

Unlike a typical electronic device that works independently of the user, a radionics machine is inherently interactive. The operator's focused intention, often enhanced through meditation or visualization, is considered a critical component of the circuit. Many experienced builders emphasize that the machine is simply a tool that helps the operator concentrate their will and direct subtle energy. This means that when you learn how to build a radionics machine, you are also learning how to calibrate your own mental and emotional state. The device does not work in isolation; it works with you.

## ESSENTIAL COMPONENTS FOR A BASIC RADIONICS DEVICE

Building a radionics machine does not require exotic parts. Most components can be sourced from electronics hobby stores or online retailers. Below is a detailed breakdown of what you will need to construct a simple yet effective "rate selector" device, which is the most common type of homemade radionics machine.

### Main Circuit Board and Enclosure

- **Enclosure:** A wooden or metal box approximately 6x8x3 inches. Wood is preferred by many builders for its insulating properties and natural feel, but a metal case can provide shielding from electromagnetic interference.
- **Grounding Plate:** A copper or brass plate (around 4x4 inches) that serves as the witness plate where you place a sample of the subject (like a photo, hair, or blood spot).
- **Output Plate:** A similar copper or brass plate where the treated item (like a water bottle or pendulum) is placed to receive the broadcast frequencies.

### Rate Selection and Tuning Controls

- **Variable Resistors (Potentiometers):** Three to four 1M ohm linear taper potentiometers are typically used. These allow you to dial in specific frequencies or rates. Some advanced designs use ten-turn potentiometers for finer resolution.
- **Rotary Switches:** A 12-position rotary switch can be used to select different frequency ranges or operational modes.
- **Capacitors and Inductors:** A selection of ceramic capacitors (100pF to 0.1uF) and a variable inductor (often wound on a ferrite core) help create resonant circuits that can be tuned to specific frequencies.

### Signal Generation and Detection

- **555 Timer IC:** This is the workhorse of many homemade radionics machines. It can be configured to generate a wide range of frequencies from a few hertz to several kilohertz.
- **Transistors:** NPN transistors like the 2N3904 or BC547 can be used to amplify the signal. A simple two-transistor oscillator circuit is very effective.
- **LED Indicator:** A red or green LED with a current-limiting resistor provides visual feedback that the circuit is powered and oscillating.
- **Battery:** A 9V battery or a small 12V power supply is sufficient for most designs. Battery power is often preferred to avoid mains interference.

## STEP-BY-STEP GUIDE: HOW TO BUILD RADIONICS MACHINE

Now that you understand the components, let us walk through the actual assembly process. This

guide assumes you have basic soldering skills and can read a simple schematic. If you are completely new to electronics, consider starting with a pre-made kit or a very simple circuit before attempting a more complex build.

### Step 1: Prepare the Enclosure and Plates

Begin by drilling holes in your chosen enclosure. You will need holes for the potentiometers, rotary switch, LED, and output jack if you plan to connect an external antenna. Mount the copper witness plate on the inside of the lid or on the top surface of the box. The output plate should be mounted on the bottom or side. Some builders also add a small copper "stick plate" that connects to the circuit and acts as a hand contact for the operator to complete the circuit. Use silicone adhesive or small brass screws to secure the plates, ensuring good electrical contact with the ground wire.

### Step 2: Assemble the Oscillator Circuit

The core of your radionics machine is an adjustable oscillator. The 555 timer IC is an excellent choice for beginners. Connect pin 1 to ground, pin 8 to positive voltage, and pins 2 and 6 together. Connect a 10kOhm resistor from pin 7 to positive voltage, and a 1MOhm potentiometer (wired as a variable resistor) from pin 7 to pins 2 and 6. Connect a 0.1uF capacitor from pins 2 and 6 to ground. The output on pin 3 will now produce a square wave whose frequency is controlled by the potentiometer. This adjustable frequency is your "rate" control.

For a more sophisticated design, add a second 555 timer or a transistor buffer stage to shape the output wave into a smoother sine-like form. Many traditional radionics designs use a "rubbing plate" or "stick pad" as the primary interface, which creates a tactile feedback loop. The stick plate is connected to the output of the oscillator through a current-limiting resistor, allowing the operator to feel a slight tingle or resistance as they adjust the potentiometer.

### Step 3: Wire the Rate Selectors and Switches

Wire your potentiometers in series or parallel, depending on the complexity you desire. A common configuration uses three potentiometers: one for coarse frequency adjustment, one for fine tuning, and a third for intensity or "broadcast power." The rotary switch can be used to select different capacitor values, effectively changing the frequency range of the oscillator. For example, position 1 might give you 1-100 Hz, position 2 gives 100-1000 Hz, and so forth. This allows you to cover a wide spectrum of rates useful for different types of treatments.

### Step 4: Connect the Witness and Output Plates

The witness plate is typically connected to the input side of the circuit, often through a high-value resistor (10MOhm) to ground. This creates a sensitive impedance bridge. The output plate is connected to the output of the oscillator, usually through a series capacitor to block DC current. Some builders also add a small antenna (a simple telescoping rod or a coil of wire) to broadcast the frequencies more effectively into the environment. The antenna can be connected to the output plate through a switch so you can toggle between direct contact broadcast and remote broadcast.

### Step 5: Test and Calibrate Your Device

Once the circuit is assembled, test it with a multimeter to ensure you have proper voltage at all key points. Connect a small speaker or earphone to the output to hear the oscillation frequency. Adjust the potentiometers and listen for smooth, continuous changes in pitch. Now, place a witness (like a hair sample from a friend) on the witness plate and a glass of water on the output plate. Set your intention for the water to be "energized" or "balanced." Run the device for 10-15 minutes while focusing on your intent. This is a basic calibration and testing procedure. Over time, you will develop your own intuitive sense of what settings work best for different situations.

## ADVANCED FEATURES AND MODIFICATIONS

Once you have mastered the basic design, you can explore more advanced features to enhance your radionics machine's capabilities. These modifications allow for greater precision and flexibility.

### Adding a Digital Frequency Counter

Instead of relying on dial markings, you can add a small digital frequency counter module to your device. These inexpensive modules display the exact frequency being generated, allowing you to use precise numerical rates from radionics reference books. This turns your analog device into a hybrid analog-digital tool, combining the tactile feel of knobs with the accuracy of digital readout. The frequency counter can be connected to the output of the oscillator through a buffer amplifier to avoid loading the circuit.

### Multiple Output Channels

Some advanced designs include two or three independent oscillator channels, each with its own witness and output plate. This allows you to broadcast multiple frequencies simultaneously, which is useful for complex imbalances that require a harmonic blend of rates. You can use separate 555 timers for each channel, or use a single microcontroller to generate multiple frequencies at once. This is a logical next step after you have successfully built your first single-channel machine.

### Using a Microcontroller Like Arduino

For the tech-savvy builder, replacing the analog oscillator with an Arduino or Raspberry Pi Pico opens up endless possibilities. You can program the microcontroller to generate any frequency with extreme precision, store libraries of rates, and even create automated treatment sequences. The

microcontroller's output goes through a digital-to-analog converter (or a simple resistor ladder) to produce a clean sine wave. This approach is perfect for those who want to learn how to build a radionics machine that is both powerful and programmable.

**PRACTICAL TIPS FOR SUCCESSFUL OPERATION**

Operating a homemade radionics machine is as much an art as it is a science. Here are some practical tips to help you get the best results from your device.

Create a Dedicated Workspace

Designate a quiet, clean space for your radionics work. Minimize electromagnetic clutter by turning off Wi-Fi routers, mobile phones, and other electronic devices in the immediate area. Many practitioners find that working during the early morning or late evening, when ambient energies are calmer, enhances their focus. A dedicated altar or table with a simple cloth, a candle, and perhaps a crystal can help set the right energetic tone for your sessions.

Keep a Journal of Settings and Results

Radionics is inherently subjective, but keeping detailed records will help you identify patterns over time. Note the date, the witness used, the rate settings (potentiometer positions or exact frequencies), the broadcast duration, and the observed results. This journal becomes your personal radionics manual, more valuable than any commercial rate book. Over weeks and months, you will discover which frequencies are effective for different conditions and which operating techniques

yield the best outcomes.

Regularly Clean and Energize Your Machine

Your radionics machine absorbs subtle energies during use. Regularly cleanse it by wiping down the plates with a mild saltwater solution, smudging with sage, or placing it in sunlight for a few hours. Some builders also recommend running the device on a "clearing" frequency (often around 8 Hz, the Schumann resonance) for 10 minutes before each session. This resets the circuit and clears any residual energy from previous treatments, ensuring your next session starts with a clean slate.

**COMMON TROUBLESHOOTING AND FAQs**

When you learn how to build a radionics machine for the first time, you may encounter some common issues. Here are solutions to the most frequent problems.

No Signal or Weak Output

Check all solder joints and ensure that your battery is fresh. A weak output often indicates a faulty potentiometer or a capacitor that is not properly connected. Use a multimeter to trace the signal from the oscillator IC through each component. Also, ensure that your witness plate is making good contact with the sample. Sometimes simply cleaning the copper surface with vinegar or a